

Delock Active Optical USB-C™ Video Cable 4K 60 Hz 30 m

Description

This cable by Delock is suitable for connecting a USB-C™ monitor with a resolution of up to 4K Ultra HD (3840 x 2160 @ 60 Hz) to a computer with USB-C™ interface and DisplayPort alternate mode support. This active optical cable is particularly thin and can transmit signals without loss over longer distances.



Specification

- Connectors:
 - 1 x USB Type-C™ male >
 - 1 x USB Type-C™ male
- DisplayPort 1.2 specification
- Transmission of audio and video signals
- Supports DP Alt Mode
- Supports no USB data transfer and no USB charging
- Fibre optical cable with low signal degradation
- Not affected by electromagnetic interference
- Cable diameter: ca. 5.4 mm
- Contacts gold-plated
- Fixed signal direction
- Data transfer rate:
 - DisplayPort 1.2 up to 21.6 Gb/s
- Resolution up to 3840 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- Supports HDR (High Dynamic Range)
- Supports HDCP 1.4 and 2.2
- Colour: black
- Length incl. connectors: ca. 30 m

System requirements

- PC or laptop with a free USB Type-C™ port and DisplayPort alternate mode
- Monitor with a free USB Type-C™ (DP Alt Mode) interface

Package content

- USB-C™ video cable

Item no. 84132

EAN: 4043619841325

Country of origin: China

Package: • White Box

Images



| | |
|-------------------------------|--------------------------------|
| General | |
| Specification: | USB Type-C™ |
| Interface | |
| Connector 1: | 1 x USB 3.2 Gen 1 Type-C™ male |
| Connector 2: | 1 x USB 3.2 Gen 1 Type-C™ male |
| Technical characteristics | |
| Data transfer rate: | 21,6 Gb/s |
| Maximum screen resolution: | 3840 x 2160 @ 60 Hz |
| Physical characteristics | |
| Cable colour: | black |
| Cable diameter: | 5.4 mm |
| Cable length incl. connector: | 30 m |
| Smallest bending radius: | 20 mm |