

568B	Pin out	568B
white-orange	1	1
orange	2	2
white-green	3	3
green	6	6
blue	4	4
white-blue	5	5
white brown	7	7
brown	8	8
shell		shell

Fig3




Fig 4

Wirewin[®]
European Cabling Solutions

1: Electrical test

1.1 100% short and open test, miss wire test

1.2 Insulation resistance: DV 300V 500M Ohm Min



1.3 TIA/EIA Channel test by Fluke tester, random test, 250Mhz ,

1.4 568B-568B pin out

2: All material are RoHS compliant

3: print: as per customer's request except illegal request

Part No	Name	Specification	Qty
1	Cable	S/FTP Cat6 4pair, Cu 27AWG 7*0.127mm, PVC jacket, OD 5.6+/- 0.2	
2	Connector	8P8C RJ45 plug, 3u"gold plated Pins, shielded, red color	2
3	Boot	Wirewin boot type,	2
4	Polybag	WIREWIN bag,	1
5	cable tie	same color cable tie	2
6	Label	black print, white background	1

 European Cabling Solutions			
Product	S/FTP CAT6 27AWG CU PATCH CORD		
Part No	PKW-PIMF KAT6	ICON	Toerance
Drawn by			x. +/- 1.00
Checked by			X.X +/- 0.50
Approved by			Scale mm
Version	A	Date	20141212